WLDH系列螺带混合机

WLDH Series Ribbon Mixer

▶ 用途 (Application)

螺带混合机一般用于粘性或有凝聚性的粉粒体的混合以及粉粒体中添加液体及糊状物料的混合,同时由于粘性物料清洗困难的特点,适用于产量大、 不经常变换品种的场合混合。装载系数大、设备占地面积小。

WLDH Series Horizontal Ribbon Mixer is generally used in the mixing of viscous or adhesive powder material, or the mixing of powder which needs to add liquid, and paste material, Meanwhile, because it is difficult to clean viscous material, the machine is suitable for the mixing case, where the output is large and there is no need of displacing material variety frequently. It has a big loading coefficient and a small occupied area.



▶ 特点 (Features)

卧式螺带混合机由U形容器、螺带搅拌叶片和传动部件组成;螺带状叶片一般做成双层或三层,外层螺旋将物料从两侧向中间汇集,内层螺旋将物料从中间向两侧输送,形成对流混合。螺带混合机对于粘性或有凝聚性的粉粒体的混合以及粉粒体中添加液体及糊状物料的混合有良好结果,筒盖可做成全开式门,以便于对设备进行清洗替换产品。

WLDH Series Horizontal Ribbon Mixer is a high efficiency horizontal ribbon mixer. WLDH Ribbon Mixer comprises of U-shaped container, transmission parts and ribbon agitating blades which usually have double or triple layers with outside screw gathering the material from sides to center and inside screw transmitting the material from center to sides to form convection mix, Ribbon mixer has a good result in the mix of viscosity or cohesion powder and of putting liquid and mash material into the powder. The cylinder cover can be fully open so as to clean and change the products.







▶ 技术参数(Technical Parameters)

型号TYPE	全容积 All Volume (m³)	装载系数 Loads Coefficient	功率 Power (kw)	外形尺寸 Overall Size (mm)	机器净重 Net Weight (kg)
WLDH -0.1	0.1	0.4-0.6	3	1190*740*770	330
WLDH -0.3	0.3		4	2030*630*980	720
WLDH -0.5	0.5		7.5	2320*730*1130	980
WLDH -1	1		11	2800*920*1320	1700
WLDH -1.5	1.5		11	3180*1020*1550	1800
WLDH -2	2		15	3310*1120*1640	2100
WLDH -3	3		18.5	3750*1290*1820	3000
WLDH -4	4		22	4220*1400*1990	3980
WLDH -5	5		22	4220*1500*2190	4620
WLDH -6	6		30	4700*1610*2260	6180
WLDH -8	8		37	4420*2150*2470	8200
WLDH -10	10		45	5520*2960*2720	8920
WLDH -12	12		45	5520*2960*2720	9520
WLDH -15	15		55	5840*3540*2940	9950